

an active filler having unsaturated bonds and carbon black in a specific ration to polychloroprene and useful as a sheath material.

CONSTITUTION: (A) 1-20 pts. wt. of an unsaturated bond-containing filler (e.g. magnesium methacrylate) and (B) 10-50 pts. wt. of carbon black having an average particle size of (less than)85(μ)m are added to (C) polychloroprene rubber composition containing (D) a vulcanizing agent, a vulcanization accelerator, a filler and an auxiliary to provide the objective composition.

COPYRIGHT: (C)1992,JPO&Japio

NO-DESCRIPTORS .

22. PRODUCTION OF WATER-ABSORBENT RESIN WITH EXCELLENT HEAT RESISTANCE

PAJ 00-29-76 03014809 JP NDN- 190-0057-0905-3



INVENTOR(S)- KOJI, KATO; KENSHO, FUJITANI; KENJI, TOKIMURA

PATENT APPLICATION NUMBER- 01150207

DATE FILED- 1989-06-13

PUBLICATION NUMBER- 03014809 JP

DOCUMENT TYPE- A

PUBLICATION DATE- 1991-01-23

INTERNATIONAL PATENT CLASS- C08F22004; C08F22004

APPLICANT(S)- MITSUBISHI PETROCHEM CO LTD

PUBLICATION COUNTRY- Japan

PURPOSE: To obtain the subject resin improved in the thermal stability in an aqueous gel state by polymerizing a specified polymerizable monomer mixture in an aqueous medium in the presence of a water-soluble divinylc monomer and a water-soluble radical polymerization initiator.

CONSTITUTION: A polymerizable monomer mixture, e.g. a mixture of sodium acrylate with magnesium acrylate , wherein at least 20% of the total carboxyl groups of the acrylic acid monomers are neutralized with alkali metal and magnesium salts and a molar ratio of the alkali metal salt to the magnesium salt is 1:9 to 9:1, is polymerized in an aqueous medium at 25-150 (degree sign)C in the presence of 0.01-5wt.% (based on the above mixture) of a water-soluble divinylc monomer, e.g. N,N-methylenebis(meth)acrylamide, and a water-soluble radical polymerization initiator, e.g. 2,2'-azobis(2-amidinopropane) dihydrochloride.

COPYRIGHT: (C)1991,JPO&Japio

NO-DESCRIPTORS .

23. ELASTOMER COMPOSITION

PAJ 00-28-76 01282238 JP NDN- 190-0024-1133-8

BEST AVAILABLE COPY